



PRODUCT SPECIFICATION FORM
HARRINGTON THREE-PHASE ELECTRIC CHAIN HOISTS

NER/ER THREE-PHASE ELECTRIC CHAIN HOISTS/TROLLEYS

Quantity _____
Capacity _____
Lift _____
Lift Speed _____ C (Common) _____ L (Low)
_____ S (Standard) _____ H (High)
_____ Single _____ Dual
Voltage _____ 208-3-60 _____ 230-3-60 _____ 460-3-60 _____ 575-3-60
Control Voltage _____ 110V (standard) _____ 24V
Control _____ Pendant
Pendant Drop _____ (standard is 4' less than lift)
Power Supply Cord _____
(standard is 15' thru 5 Ton – hook, push or geared trolley mount)
(standard is 30' above 5 Ton – hook, push or geared trolley mount)
(standard is 30' all capacities – motorized trolley mount)
Suspension _____ Hook _____ Lug _____ Trolley (see below)

Options: _____ Canvas Chain Container
_____ Steel Chain Container
_____ Plastic Chain Container
_____ Mechanical Brake (ER standard feature)
_____ Hoist Mount – Parallel to Beam
_____ Hoist Mount – Perpendicular to Beam

Trolley Type _____ Push _____ Geared _____ Motorized
Hand Chain Drop _____ (if geared trolley)
Travel Speed _____ L (40 FPM) _____ S (80 FPM) _____
_____ SD (80/13 FPM) (if motorized trolley)
Beam Type/Size _____
Beam Flange Width _____
Beam Radius _____ (if curved monorail)

Specials: _____

Form completed by:
(* indicates required field)

*Name _____ Company _____

*Phone _____ Fax _____

*Address _____ *City _____ *State _____ *Zip _____

*E-Mail Address _____

Copy & fax to 717-665-7432