

PRODUCT SPECIFICATION FORM

HARRINGTON ELECTRIC WIRE ROPE PRODUCTS

RH THREE-PHASE ELECTRIC WIRE ROPE HOISTS/TROLLEYS

Quantity _____
 Capacity _____
 Lift _____
 Headroom Needed _____
 Configuration _____ D (Deck/Base Mounted or Lug Suspended Hoist)
 _____ S (Standard Headroom Trolley Hoist)
 _____ U (Ultra-Low Headroom Trolley Hoist)
 Hoist Speed _____ Single _____ Dual
 Trolley Speed _____ Single - _____ 40 FPM _____ 64 FPM _____ 80 FPM
 _____ Dual - _____ 64/16 FPM _____ 80/20 FPM
 Voltage _____ 230-3-60 _____ 460-3-60
 Control Voltage 110V
 Beam Type/Size _____
 Beam Flange Width _____
 Beam Radius _____ (if curved monorail)

Options: _____ Special Voltage _____
 _____ Pendant and Pendant Cord
 Specify Drop _____
 Choose _____ Unwired _____ Installed
 _____ Power Supply Cord
 Specify Length _____
 Choose _____ Unwired _____ Installed
 _____ Eye Bolt Kit
 _____ Trolley Travel Limit Switch
 _____ Weatherization (for outdoor use)

Specials: _____

Please contact Harrington's Customer Service Department for further assistance:

Location	Phone Number	Fax Number
Manheim, PA	800-233-3010	717-665-7432
Corona, CA	800-317-7111	951-279-7500

E-mail: customerservice@harringtonhoists.com

Form completed by:

Name _____ Company _____

Phone _____ Fax _____