

PRODUCT SPECIFICATION FORM

HARRINGTON SINGLE-PHASE ELECTRIC CHAIN HOISTS

SNER SINGLE-PHASE ELECTRIC CHAIN HOISTS/TROLLEYS

Quantity _____
 Capacity _____
 Lift _____
 Lift Speed _____ C (Common) _____ L (Low) _____ S (Standard)
 (no dual speed available)
 Voltage _____ 115-1-60 _____ 230-1-60
 Control Voltage 115V
 Pendant Drop _____ (standard is 4' less than lift)
 Power Supply Cord _____
 (standard is 15' – hook, push or geared trolley mount)
 (standard is 30' – motorized trolley mount)
 Suspension _____ Hook _____ Lug _____ Trolley (see below)

Options: _____ Canvas Chain Container
 _____ Steel Chain Container
 _____ Plastic Chain Container
 _____ Hoist Mount – Parallel to Beam
 _____ Hoist Mount – Perpendicular to Beam

Trolley Type _____ Push _____ Geared _____ Motorized
 Hand Chain Drop _____ (if geared trolley)
 Travel Speed _____ L (40 FPM) _____ S (80 FPM)
 (no dual speed available)

Beam Type/Size _____
 Beam Flange Width _____
 Beam Radius _____ (if curved monorail)

Specials: _____

ED SINGLE-PHASE ELECTRIC CHAIN HOISTS/TROLLEYS

Quantity _____
 Capacity _____
 Lift _____
 Lift Speed _____ S (Single) _____ DS (Dual) _____ DA (Dual Adjustable)
 Voltage 120-1-60
 Control Voltage 120V
 Pendant Drop _____ (for S and DS speeds – standard is 3' less than lift)
 Power Supply Cord _____ (standard is 16')
 Chain Container Plastic container is standard
 Suspension _____ Hook _____ Trolley (see below)

Trolley Type _____ Mini Push Trolley _____ Push _____ Geared
 Hand Chain Drop _____ (if geared trolley)
 Beam Type/Size _____
 Beam Flange Width _____
 Beam Radius _____ (if curved monorail)

Specials: _____

Please contact Harrington's Customer Service Department for further assistance:

Location	Phone Number	Fax Number
Manheim, PA	800-233-3010	717-665-7432
Corona, CA	800-317-7111	951-279-7500

E-mail: customerservice@harringtonhoists.com

Form completed by:

Name _____ Company _____

Phone _____ Fax _____