

Harrington Hoists, Inc.
 401 West End Avenue
 Manheim, PA 17545
 United States of America
 TEL: 1-717-665-2000
 FAX: 1-717-665-2861

Product:

- Manual Chain Hoist:** **RCB (CB ATEX series)**
- Geared Trolley:** **RGTS (GTS ATEX series)**
- Plain Trolley:** **RPTS (PTS ATEX series)**
- Combined products:** **RCB with RGTS (lug or hook mounted)**
 RCB with RPTS (lug or hook mounted)

Serial No(s): _____

The undersigned hereby declares, on behalf of Harrington Hoists, Inc., a legal subsidiary of the KITO Corporation (of Nakakoma-gun, Yamanashi, Japan), that the above referenced product, to which this declaration relates complies with the provisions of the ATEX directive 2014/34/EU, proved by compliance with the following standards.

Standards:

- | | |
|-----------------|--|
| EN 13463-1:2009 | Non-electrical equipment for use in potentially explosive atmospheres. Basic method and requirements |
| EN 13463-5:2009 | Non-electrical equipment for use in potentially explosive atmospheres. Protection by constructional safety 'c' |

Notified Body to whom technical documentation is deposited: PTB, Identification No. 0102
 Registration number: 11 ATEX D080

Notes:

This product is based on CB, model M3 (refer to D/C M3-1207-E-02) and TSP/TSG, model TS2 and TS1 (refer to D/C TS-1207-E-02)

Product is marked

RCB Hoist: <div style="display: flex; align-items: center; margin-top: 5px;"> Ex II 2G c IIB T4 Ex II 2D c T135°C </div>	RGTS/RPTS Trolley <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; padding: 2px;"> For T4* hoist: <div style="display: flex; align-items: center; margin-top: 2px;"> Ex II 2G c IIB T4 Ex II 2D c T135°C </div> </td> <td style="width: 50%; padding: 2px;"> For T5* hoist: <div style="display: flex; align-items: center; margin-top: 2px;"> Ex II 2G c IIB T5 Ex II 2D c T100°C </div> </td> </tr> </table>	For T4* hoist: <div style="display: flex; align-items: center; margin-top: 2px;"> Ex II 2G c IIB T4 Ex II 2D c T135°C </div>	For T5* hoist: <div style="display: flex; align-items: center; margin-top: 2px;"> Ex II 2G c IIB T5 Ex II 2D c T100°C </div>
For T4* hoist: <div style="display: flex; align-items: center; margin-top: 2px;"> Ex II 2G c IIB T4 Ex II 2D c T135°C </div>	For T5* hoist: <div style="display: flex; align-items: center; margin-top: 2px;"> Ex II 2G c IIB T5 Ex II 2D c T100°C </div>		

* Trolley by itself is rated for T5 temperature class. When used with a T4 rated hoist, trolley marking shall be T4.

Drew Schoenberger
 Manager of Engineering & Manufacturing